RUGER 22/45 MARK III NO. KP512MKIII, \$398

☐ Gun Tests RecommendS: don't buy ☐

With each shot the narrow grip worked better in our hands, but an overly complex take down/reassembly procedure might ultimately keep this gun in the closet.

SPECIFICATIONS

01 2011 107111	0110
OVERALL LENGTH	9.5 IN.
BARREL LENGTH	5.5 IN.
SIGHT RADIUS	7.9 IN.
OVERALL HEIGHT	5.5 IN.
FRONT STRAP HEIGHT	2.6 IN.
BACK STRAP HEIGHT	3.0 IN.
WEIGHT UNLOADED	31.5 oz.
CAPACITY	10+1 ROUNDS
MAXIMUM WIDTH	1.1 IN.
GRIP THICKNESS (MAX)	0.9 IN.
GRIP CIRCUMFERENCE (MAX)	5.3 IN.
FRAME MATERIAL/FINISH	. POLYMER/BLACK
Barrel	STAINLESS STEEL
SLIDE MATERIAL/FINISH STAINLES	S STEEL/POLISHED



GRIP MATERIAL/FINISH POLYMER/ BLACK CHECKERED
TRIGGER PULL WEIGHT SINGLE ACTION 4.0 LBS.
TRIGGER SPAN SINGLE ACTION 2.5 IN.
WARRANTYLIFETIME
TELEPHONE (603) 863-3300
WEBSITE OR EMAILWWW.RUGER-FIREARMS.COM

The Ruger 22/45 Mark III came with a scope mount that was simple to install. The receiver was drilled and tapped, and the rear sight could be left in place.

