

## ACCURACY AND CHRONOGRAPH DATA

<b>Hornady 380 ACP 90-gr. Z-Max</b>	<b>Walther PK380 Laser</b>	<b>Ruger LCP-LM</b>	<b>SIG P238 TL</b>
Average Velocity	941 fps	881 fps	904 fps
Muzzle Energy	177 ft.-lbs.	155 ft.-lbs.	163 ft.-lbs.
Average Group	1.1 in.	1.1 in.	1.9 in.

<b>Hornady 380 ACP 90-grain XTP</b>	<b>Walther PK380 Laser</b>	<b>Ruger LCP-LM</b>	<b>SIG P238 TL</b>
Average Velocity	965 fps	873 fps	904 fps
Muzzle Energy	186 ft.-lbs.	152 ft.-lbs.	163 ft.-lbs.
Average Group	1.6 in.	1.3 in.	1.7 in.

<b>PPU 380 ACP 94-grain FMJ</b>	<b>Walther PK380 Laser</b>	<b>Ruger LCP-LM</b>	<b>SIG P238 TL</b>
Average Velocity	732 fps	703 fps	867 fps
Muzzle Energy	112 ft.-lbs.	103 ft.-lbs.	157 ft.-lbs.
Average Group	1.1 in.	1.9 in.	1.7 in.

*To collect accuracy data, we used the guns' open sights to fire five-shot groups from a bench using a rest. Distance: 15 yards. We recorded velocities using a ProChrono digital chronograph set 10 feet from the muzzle.*

<b>SPECIFICATIONS</b>	<b>Walther PK380 Laser</b>	<b>Ruger LCP-LM</b>	<b>SIG P238 TL</b>
<b>Action Type</b>	Semi-Auto, DA/SA	Locked-Breech Semi-Auto	Blowback Semi-Auto
<b>Overall Length</b>	6.5 in.	5.2 in.	5.5 in.
<b>Overall Height</b>	5.2 in.	3.6 in.	3.9 in.
<b>Overall Width</b>	1.2 in.	0.8 in.	1.3 in.
<b>Weight Unloaded/ Barrel Length/Twist</b>	19.4 oz./22.2 oz. 3.7 in., Steel	9.9 oz./12.1 oz. 2.75 in., 6 Grooves, 1:16 RH	16.2 oz./18.4 oz. 2.7 in.
<b>Capacity</b>	8+1	6+1	6+1
<b>Slide</b>	Black Steel	Blued Alloy Steel	Natural Stainless Steel
<b>Frame</b>	Black Steel	Black Glass-Filled Nylon	Black Anodized Alum.
<b>Frontstrap/Backstrap Length</b>	2.2 in./2.7 in.	1.3 in./1.9 in.	1.5 in./2.1 in.
<b>Grip</b>	Textured Polymer	Checkered Polymer	Textured Aluminum
<b>Grip Thickness/Circ.</b>	1.1 in./5.2 in.	1.2 in./4.5 in.	1.1 in./4.5 in.
<b>Sights/Sight Radius</b>	Drift Adj. Windage Rear/5.4 in.	Fixed/4.1 in.	SIGLites/3.7 in.
<b>Trigger Pull Weight</b>	11.0 lbs. (DA)/6.8 lbs. (SA)	7.5 lbs. (DA)	10.5 lbs. (SA)
<b>Trigger Span</b>	2.7 in. (DA)/2.4 in. (SA)	2.6 in. (DA)	2.4 in. (SA)
<b>Safety</b>	Ambi Manual Thumb	None, Single-Strike DAO	Frame-Mounted Thumb
<b>Laser</b>	Walther	LaserMax CenterFire	SIG Sauer
<b>Activation</b>	Sliding Switch	Sliding Switch	Pushbutton
<b>Master On/Off Switch</b>	No	No	No
<b>One-Hand/Ambi Activation</b>	Yes/No	Yes/Yes	Yes/Yes
<b>Automatic Shut Off</b>	No	No	No
<b>Beam Color</b>	Red	Red	Red
<b>Beam Modes</b>	Steady Beam	Steady Beam	Steady Beam
<b>Beam Intensity</b>	5mw, 633nm	5mw, 633nm	5mw, 633nm
<b>Dot Size</b>	0.5 in. @ 50 ft.	0.5 in. @ 50 ft.	0.5 in. @ 50 ft.
<b>Sight Adjustments</b>	Windage, Elevation	Windage, Elevation	Windage, Elevation
<b>Battery</b>	(2) SR44W	(1) 1/3 N-cell Lithium	(1) CR1/3N Lithium
<b>Battery Life</b>	4.0 hrs.	5.0 hrs.	4.0 hrs.
<b>Warranty</b>	1 Year	Lifetime	None Written
<b>Telephone</b>	(800) 372-6454	(603) 836-3300	(603) 772-2302
<b>Website</b>	WaltherAmerica.com	Ruger.com	SIGSauer.com
<b>Made In</b>	Germany	USA	USA
<b>CA, MA Approved</b>	NA	No	No/Yes (238M)