

AR-24 PISTOL COMPACT NO. 24K-13 9MM LUGER, \$550

GUN TESTS GRADE: B+

Great gun — shot accurately and to point of aim at 15 yards. Comfortable to hold and fire. Double-stack grip width a problem for small-handed shooters. Heavy for carry, in our opinion.



Action..... Locked Breech Semi-Auto, DA/SA
Overall Length..... 7.5 in.
Overall Height..... 5.2 in.
Maximum Width..... 1.5 in.
Weight Unloaded..... 36.2 oz.
Weight Loaded..... 42.4 oz.
Capacity (as tested)..... 15+1
Barrel..... 3.89 in., Alloy Steel, Ramped
6 Groove, 1:16 RH Twist
Slide..... Manganese Phosphated Steel,
Rear Serrations
Frame..... Manganese Phosphated Steel
Grip..... Checkered Rubber
Grip Thickness (max)..... 1.5 in.
Grip Circumference (max)..... 5.8 in.
Grip Frontstrap..... 2.1 in. Tall, Vertical Serrations
Grip Backstrap..... 3.0 in. Tall, Vertical Serrations
Sight Radius..... 5.25 in.

Sight, Front..... Front Blade, 1 Dot Luminous,
Dovetailed, Roll Pinned
Sight, Rear..... Fixed 2 Dot Luminous,
Combat Style, Drift Adjustable
Trigger Pull Weight (Double Action)..... 12.0 lbs.
Trigger Pull Weight (Single Action)..... 4.5 lbs.
Trigger Span (Double Action)..... 3.1 in.
Trigger Span (Single Action)..... 2.6 in.
Safety..... Frame-Mounted Left-Side Lever,
Half Cock, Internal Firing Pin Block
Magazines..... (2) 13-Round Blued Steel,
Removable Basepad
Accessories..... Plastic Pistol Case, Lock,
Manual, Cleaning Brushes
Warranty..... 5 Year Limited
Telephone..... (800) 336-0184
Website..... ArmaLite.com
Made By/In..... Sarsilmaz, Turkey

Getting the gun to this point is pretty easy: line up two marks, remove the slide-stop pin, push the slide off the frame. Slide and frame are CNC-machined from ordnance alloy steel. Barrel rifling is broached rather than button rifled. The hammer is a Commander-style shape with a rounded spur. The exterior finish showed minor wear marks in the epoxy topcoat. The matte-black (or dark grey) reduced glare on the top of the slide. Slide-to-frame fit was tight.

