

PERFORMANCE TABLE

Winchester 115-gr. Silvertip	Taurus P-111	S&W SW9M	Kel-Tec P-11
Average Velocity at 15 ft.	1,157 fps	1,107 fps	1,123 fps
Standard Deviation	8 fps	6 fps	16 fps
Average Muzzle Energy	342 ft-lbs	313 ft-lbs	322 ft-lbs
Smallest Group at 7 yds.	0.50 inches	2.38 inches	1.50 inches
Largest Group Size	1.50 inches	3.50 inches	2.13 inches
Average Group Size	1.00 inches	2.78 inches	1.75 inches
Federal 124-gr. Hydra-Shok			
Average Velocity at 15 ft.	1,052 fps	987 fps	1,028 fps
Standard Deviation	31 fps	20 fps	14 fps
Average Muzzle Energy	305 ft-lbs	268 ft-lbs	291 ft-lbs
Smallest Group at 7 yds.	0.38 inches	1.50 inches	1.13 inches
Largest Group Size	1.50 inches	2.38 inches	2.00 inches
Average Group Size	1.13 inches	2.20 inches	1.55 inches
UMC 115-gr. Metal Case			
Average Velocity at 15 ft.	1,112 fps	1,051 fps	1,084 fps
Standard Deviation	14 fps	19 fps	8 fps
Average Muzzle Energy	316 ft-lbs	282 ft-lbs	300 ft-lbs
Smallest Group at 7 yds.	1.13 inches	2.00 inches	1.00 inches
Largest Group Size	2.00 inches	3.25 inches	1.50 inches
Average Group Size	1.50 inches	2.38 inches	1.28 inches

Accuracy testing consisted of five consecutive 5-shot groups with each load.
 fps=feet per second. ft-lbs=foot-pounds