

**RUGER SR40 BSR40 40 S&W, \$525**

**GUN TESTS GRADE: B**

Score it higher if a natural point is your first priority, but we'd still like better access to the thumb safeties.



**SPECIFICATIONS**

Overall Length .....	7.55 in.
Barrel Length .....	4.14 in.
Sight Radius .....	6.0 in.
Overall Height .....	5.5 in.
Front Strap Height .....	2.4 in.
Back Strap Height .....	3.5 in.
Weight Unloaded .....	21.6 oz.
Weight Loaded (180-gr) .....	32.0 oz.
Capacity .....	15+1
Maximum Width .....	1.3 in.
Grip Thickness (Max) .....	1.15 in.
Grip Circumference (Max) .....	5.5 in. / 5.8 in.
Frame .....	Black Glass-Filled Nylon
Barrel .....	Stainless Steel
Slide .....	Nitrodox Pro Black Alloy Steel
Grip .....	Black Glass-Filled Nylon
Trigger Pull Weight Double Action .....	5.25 lbs.
Trigger Span Double Action .....	2.65 in.
Warranty .....	Lifetime
Telephone .....	(603) 863-3300
Website .....	www.Ruger-Firearms.com



**Left:** With the action cocked, the striker indicator was clearly visible from the rear of the slide, arrow. The slide carried a three-dot sight system dovetailed into place front and rear. The stealth Nitrodox Pro black color offers a reduced profile.



**Right:** Changes from the first SR pistol we tested in 2007 include the trigger-mounted safety, squared and checkered magazine-release buttons, and a slide-stop latch that curved into the frame.

**Right:** The thin grip was backed by a reversible rubber insert held by a solid pin. One side offered a flat profile to the backstrap and the other (shown) extended the grip into the hollow of the shooter's palm.



**Right,** windage adjustment required loosening the recessed Allen screw, top arrow, and drifting the entire unit left or right. The rear sight was elevation adjustable. Bottom arrow: The loaded-chamber indicator tilted up for visual and tactile confirmation. The print was overkill in our view.

