

Ruger 10/22 RB, 10/22 RP

Retail Price...\$225



SPECIFICATIONS (RB)

Warranty: None Written

METAL FINISH	Blued	REAR SIGHT TYPE	FOLDING
WEIGHT (EMPTY)	5 lbs.	CAPACITY	10 rds.
OVERALL LENGTH	37.25 in.	STOCK MATERIAL	Hardwood
BARREL LENGTH	18.5 in.	ACTION TYPE	Semiauto
SIGHT RADIUS	15 in.	TRIGGER PULL WEIGHT ...	7.5 lbs.

Our recommendation: Both guns badly need updating.

SPECIFICATIONS (RP)

Warranty: None Written

METAL FINISH	Blued	REAR SIGHT TYPE	FOLDING
WEIGHT (EMPTY)	5 lbs.	CAPACITY	10 rds.
OVERALL LENGTH	37.25 in.	STOCK MATERIAL	Polymer
BARREL LENGTH	18.5 in.	ACTION TYPE	Semiauto
SIGHT RADIUS	15 in.	TRIGGER PULL WEIGHT ...	7.2 lbs.

continued from page 15
plastic-stocked gun recording a best average group size of 0.7 inches at 25 yards with Lapua Dominator, and 0.9-inch groups with Federal UltraMatch. Naturally, it didn't shoot as well with a non-

target load, printing 1.5-inch groups with Remington Viper high-velocity rounds. The Sporter didn't do as well, however, shooting a best-group average of 1.3 inches with Eley Tenex.

In the hands, the Remingtons

showed their strengths. The action operated solidly on both guns, with the bolt sliding forward on two rails. It opened and closed with a solid "snink" sound. Their stocks, which are half an inch longer than the Rugers', also have a swell in the

Accuracy & Chronograph Data

	Lapua Dominator	RWS R50	Eley Target	Federal Ultramatch	Remington Viper
RUGER 10/22RB					
Average Velocity at 10 ft.	1,050 fps	1,051 fps	1,077 fps	1,128 fps	1,124 fps
Standard Deviation	9 fps	22 fps	6 fps	7 fps	22 fps
Smallest Group at 50 yds.	0.7 in.	0.7 in.	0.8 in.	0.9 in.	1.5 in.
Largest Group Size	0.9 in.	1.1 in.	0.9 in.	1.1 in.	2.2 in.
Average Group Size	0.8 in.	0.9 in.	0.9 in.	1.0 in.	1.9 in.
RUGER 10/22RP					
Average Velocity at 10 ft.	1,049 fps	1,034 fps	1,048 fps	1,109 fps	1,065 fps
Standard Deviation	9 fps	19 fps	11 fps	9 fps	54 fps
Smallest Group at 50 yds.	0.6 in.	0.8 in.	0.8 in.	1.6 in.	1.2 in.
Largest Group Size	0.8 in.	1.5 in.	1.3 in.	2.0 in.	1.9 in.
Average Group Size	0.7 in.	1.0 in.	1.0 in.	1.7 in.	1.4 in.
REMINGTON 597					
Average Velocity at 10ft.	1,058 fps	1,077 fps	1,030 fps	1,123 fps	1,099 fps
Standard Deviation	19 fps	17 fps	13 fps	6 fps	46 fps
Smallest Group at 50 yds.	0.6 in.	0.8 in.	0.8 in.	0.8 in.	1.1 in.
Largest Group Size	0.7 in.	1.3 in.	1.2 in.	1.1 in.	1.8 in.
Average Group Size	0.7 in.	1.0 in.	1.0 in.	0.9 in.	1.5 in.
REMINGTON 597 SPORTER					
Average Velocity at 10 ft.	1,049 fps	1,087 fps	1,048 fps	1,119 fps	1,124 fps
Standard Deviation	12 fps	2 fps	15 fps	12 fps	22 fps
Smallest Group at 50 yds.	1.2 in.	0.7 in.	1.3 in.	0.8 in.	1.0 in.
Largest Group Size	1.7 in.	2.3 in.	1.4 in.	2.3 in.	1.7 in.
Average Group Size	1.4 in.	1.6 in.	1.3 in.	1.4 in.	1.4 in.